




Diagramma di portata - Load diagrams - Curvas de cargas - Lastkurven - Courbes de charges - Грузоподъёмные характеристики

RTM 200 L - 10 NORMAL																
	(t)	m	27,70	30,50	33,40	36,30	39,20	42,10	45,00	47,90	50,80	53,70	56,60	59,50	62,40	65,30
	10	16,48	5,66	5,08	4,58	4,16	3,80	3,49	3,22	2,98	2,77	2,58	2,42	2,26	2,13	2,00
	10	16,91	5,83	5,23	4,72	4,29	3,92	3,60	3,32	3,08	2,86	2,67	2,50	2,34	2,20	
	10	17,79	6,17	5,54	5,00	4,55	4,16	3,82	3,53	3,27	3,05	2,85	2,66	2,50		
	10	17,99	6,25	5,61	5,06	4,60	4,21	3,87	3,58	3,32	3,09	2,88	2,70			
	10	18,07	6,28	5,64	5,09	4,63	4,23	3,89	3,60	3,34	3,11	2,90				
	10	18,28	6,36	5,71	5,16	4,69	4,29	3,95	3,65	3,38	3,15					
	10	18,58	6,48	5,82	5,25	4,78	4,37	4,02	3,72	3,45						
	10	18,93	6,61	5,94	5,36	4,88	4,47	4,11	3,80							
	10	19,28	6,75	6,06	5,48	4,98	4,56	4,20								
	10	19,42	6,80	6,11	5,52	5,02	4,60									
	10	19,68	6,90	6,20	5,60	5,10										
	10	20,29	7,14	6,42	5,80											
	10	20,52	7,23	6,50												
	10	20,71	7,30													



Diagramma di portata - Load diagrams - Curvas de cargas - Lastkurven - Courbes de charges - Грузоподъёмные характеристики


RTM 200 L -10 M-LIFT

	(t)	m	27,70	30,50	33,40	36,30	39,20	42,10	45,00	47,90	50,80	53,70	56,60	59,50	62,40	65,30
	10	17,70	6,14	5,51	4,97	4,52	4,13	3,80	3,51	3,25	3,03	2,83	2,65	2,48	2,33	2,20
	10	18,20	6,33	5,68	5,13	4,66	4,27	3,92	3,63	3,36	3,13	2,93	2,74	2,57	2,42	
	10	19,18	6,71	6,03	5,45	4,95	4,54	4,18	3,86	3,59	3,34	3,12	2,93	2,75		
	10	19,41	6,80	6,11	5,52	5,02	4,60	4,23	3,92	3,64	3,39	3,17	2,97			
	10	19,52	6,84	6,15	5,55	5,05	4,63	4,26	3,94	3,66	3,41	3,19				
	10	19,77	6,94	6,24	5,63	5,13	4,70	4,33	4,00	3,72	3,47					
	10	20,12	7,07	6,36	5,75	5,23	4,79	4,41	4,08	3,80						
	10	20,52	7,23	6,50	5,87	5,35	4,90	4,52	4,18							
	10	20,93	7,39	6,64	6,01	5,47	5,01	4,62								
	10	21,10	7,45	6,70	6,06	5,52	5,06									
	10	21,41	7,57	6,81	6,16	5,61										
	10	22,10	7,84	7,05	6,38											
	10	22,38	7,94	7,15												
	10	22,60	8,03													

Altezza torre - Tower height - Altura torre - Turmhohe - Hauteur de la tour - ИСПОЛНЕНИЯ БАШНИ

TM21


RT1 RAP1	SERVICE	OUT OF SERVICE
R1	- 1200 kN	- 1700 kN
R2	760 kN	1310 kN
V	875 kN	



RT1
RAP1

MAX H (m)		
	FEM 1001	C 25
27,70 ->65,30	59,15	59,15

RTB	SERVICE	OUT OF SERVICE
R1	- 1450 kN	- 2400 kN
R2	980 kN	2000 kN
V	940 kN	



RTB

MAX H (m)		
	FEM 1001	C 25
27,70 ->65,30	70,95	70,95


* **Traliccio per sopraelevazione** - Section for external climbing - Treillis pour l'élévation externe - Sección para elevación externa - внешней секцией для подъема
Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us
Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage
Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter
Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Altezza torre - Tower height - Altura torre - Turmhohe - Hauteur de la tour - ИСПОЛНЕНИЯ БАШНИ

TM21

F4	SERVICE	OUT OF SERVICE
R1	- 910 kN	- 1110 kN
R2	- 80 kN	0 kN
V	765 kN	

54.35 m (FEM 1001)




F4

MAX H (m)		
	FEM 1001	C 25
27,70 ->36,30	54,35	48,45
39,20 ->65,30	48,45	42,55

FP4	SERVICE	OUT OF SERVICE
R1	- 910 kN	- 1110 kN
R2	- 80 kN	0 kN
V	765 kN	

54.95 m (FEM 1001)



FP4

MAX H (m)		
	FEM 1001	C 25
27,70 ->36,30	54,95	49,05
39,20 ->65,30	49,05	43,15

Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us

Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage


Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter

Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Altezza torre - Tower height - Altura torre - Turmhohe - Hauteur de la tour - ИСПОЛНЕНИЯ БАШНИ

TM16

RT1 RAP1	SERVICE	OUT OF SERVICE
R1	- 1500 kN	- 1500 kN
R2	1110 kN	1600 kN
V	790 kN	




MAX H (m)		
	FEM 1001	C 25
27,70 ->65,30	47,35	47,35

Altezza torre - Tower height - Altura torre - Turmhohe - Hauteur de la tour - ИСПОЛНЕНИЯ БАШНИ


TM16

F4	SERVICE	OUT OF SERVICE
R1	- 870 kN	- 880 kN
R2	- 95 kN	- 20 kN
V	730 kN	

FP4	SERVICE	OUT OF SERVICE
R1	- 870 kN	- 880 kN
R2	- 95 kN	- 20 kN
V	730 kN	



MAX H (m)		
	FEM 1001	C 25
27,70 ->36,30	48,45	42,55
39,20 ->65,30	42,55	36,65




MAX H (m)		
	FEM 1001	C 25
27,70 ->36,30	49,05	43,15
39,20 ->65,30	43,15	37,25

Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us
 Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage
 Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter
 Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Altezza torre - Tower height - Altura torre - Turmhohe - Hauteur de la tour - ИСПОЛНЕНИЯ БАШНИ

HP20

RTB1 RAP1	SERVICE	OUT OF SERVICE
R1	- 1740 kN	- 3100 kN
R2	1180 kN	2580 kN
V	1130 kN	



MAX H (m)		
	FEM 1001	C 25
27,70 -> 65,30	70,40	66,65

Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us

Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage

Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter


Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Zavorramento - Counterweight - Bloque de contrapeso - Gegengewichtsblöcke - Bloc de contrepoid - Плиты противовеса

	65,30m 62,40m/59,50m		56,60m/53,70m		50,80m/47,90m		45,00m 42,10m/ 39,20m		36,30m 33,40m/30,50m		27,70m	
	A	B	A	B	A	B	A	B	A	B	A	B
	6	2	6	1	6	0	5	1	5	0	4	1
	23100 kg		21450 kg		19800 kg		18150 kg		16500 kg		14850 kg	


Altre Installazioni - Other configurations - Otras Implantaciones - Aufstellmöglichkeiten - Autres Im-plantations - Другие варианты компоновки башни

INTERNAL CLIMBING



HP20		
	H (m)	C (m)
1		

EXTERNAL CLIMBING




TM21			
	A min/max (m)	B min/max (m)	C max (m)
all	33/45	18/30	38

HP20			
	A min/max (m)	B min/max (m)	C max (m)
1			

1 Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us
 Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage
 Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter
 Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Meccanismi - Mechanisms- Mecanismos - Antriebe - Mécanismes - Приводы




45 HVF 100		t	m/min	
 45 kW		10	0 → 23	
		4	0 → 54	
 max 430 m		2	0 → 96	
		1.4	0 → 109	

	5.5	kW	0	→	90	m/min
	2 x 5.5	kW	0	→	0.7	rpm

 2000/14/CEE 2005/88/CEE	 2006/95/CEE	400 V	50 Hz	I _{max} =	116	A	Fuse=	125	A	MACHINE RATING	MAX GENERATOR
		460 V	60Hz	I _{max} =	101	A	Fuse=	100	A	77 kVA	123 kVA

Ingombri e pesi - Dimensions and weight - Dimensões e pesos - Abmessungen und Gewicht - Encombrent et poids - Габариты, размеры и вес










(*)  65,30 m - 45HVF100







X4





X4

(*) Parte rotante - Slewing crane part - Parte rotativa - Drehender Kranteil - Partie tournante - Поворотная часть			Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Quantità Quantity Cantidad Menge Quantité Количество	Peso Weight Peso Gewicht Poids вес
Tronco braccio Jib section Elemento de flecha Auslegerelement Élément de flèche Секция стрелы	1		5,14 m	1,13 m	2,41 m	1	1480 kg
	2		6,07 m	1,13 m	2,30 m	1	1305 kg
	3		6,05 m	1,13 m	2,32 m	1	1145 kg
	4		3,15 m	1,13 m	2,31 m	1	570 kg
	5		6,05 m	1,13 m	2,36 m	1	950 kg
	6		6,06 m	1,13 m	2,24 m	1	850 kg
	7		6,06 m	1,13 m	1,84 m	1	770 kg
	8		6,05 m	1,13 m	1,71 m	1	645 kg
	9		6,05 m	1,13 m	1,71 m	1	530 kg

Ingombri e pesi - Dimensions and weight - Dimensões e pesos - Abmessungen und Gewicht - Encombrent et poids - Габариты, размеры и вес



(*) Parte rotante - Slewing crane part - Parte rotativa - Drehender Kranteil - Partie tournante - Поворотная часть			Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Quantità Quantity Cantidad Menge Quantité Количество	Peso Weight Peso Gewicht Poids вес
Tronco braccio Jib section Elemento de flecha Auslegerement Élément de flèche Секция стрелы	10		6,02 m	1,13 m	1,72 m	1	445 kg
	11		6,00 m	1,13 m	1,74 m	1	405 kg
	12		6,00 m	1,13 m	1,77 m	1	385 kg
Punta braccio - Jib point - Tramo punta de pluma - Ausleger - Kopfstück - Pointe de flèche - Концевая секция стрелы			1,16 m	0,73 m	2,27 m	1	95 kg
Argano carrello - Trolley winch - Equipo carro - Windenwagen - Treuil du chariot - лебедка тележка			0,75 m	1,12 m	1,14 m	1	315 kg
Carrello - Trolley - Carro - Laufkatze - Chariot - тележка			1,28 m	1,44 m	0,92 m	1	340 kg
Ballatoio carrello - Trolley platform - Suporte de carro - Laufkatze Podest - Palier du chariot - тележка посадки			0,91 m	0,55 m	1,85 m	1	45 kg
Cabina - Cabin - Cabina - Kabine - Кабина	FM12		2,94 m	2,20 m	2,30 m	1	990 kg
Cuspide - A-Frame - Caballette de pluma - Porte-flèche - портал стрелы			1,23 m	1,23 m	2,09 m	1	430 kg

Ingombri e pesi - Dimensions and weight - Dimensões e pesos - Abmessungen und Gewicht - Encombrement et poids - Габариты, размеры и вес

Torre - Tower - Torre - Turm - Tour - Башня		Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Peso Weight Peso Gewicht Poids вес
TM21.6		5,90 m	2,10 m	2,06 m	2600 kg
TM21 TB12		11,80 m	2,30 m	2,12 m	6470 kg
TM16.6		5,90 m	1,60 m	1,56 m	2300 kg
TM16.12		11,80 m	1,60 m	1,56 m	4430 kg
HP20 3.75		3,75 m	1,95 m	2,10 m	2972 kg
HP20 TB10		10,00 m	1,95 m	2,10 m	7000 kg

Ancoraggi - Anchors - Anclajes - Verankerungen - Anchorages - Анкера		Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Peso Weight Peso Gewicht Poids вес
TM16 RAP1 TM21 RAP1		0,43 m	0,75 m	0,75 m	240 kg
TM16 RT1 L=1135 TM21 RT1 L=1135		1,19 m	0,60 m	0,60 m	360 kg
TM16 RT1 L=1400 TM21 RT1 L=1400		1,46 m	0,60 m	0,60 m	185 kg
TM21 RTB		1,76 m	0,60 m	0,60 m	315 kg
HP20 RTB1		1,92 m	0,60 m	0,60 m	420 kg
HP20 RAP1		0,69 m	0,65 m	0,65 m	270 kg

Ingombri e pesi - Dimensions and weight - Dimensões e pesos - Abmessungen und Gewicht - Encombement et poids - Габариты, размеры и вес

Accessori - Accessories - Accesorios - Zubehör - Accessoires - аксессуары			Lunghezza Length Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Quantità Quantity Cantidad Menge Quantité Количество	Peso Weight Peso Gewicht Poids вес
Carro - Undercarriage - Carro - Fundamentkreuz - Châssis de base - 4,5mx4,5m TM16 TM21	Trave principale di base - Base main beam - Viga base principal - Fundamentkreuzträger - Poutre de chassis - Главная балка основания		6,52 m	0,95 m	1,00 m	1	2900 kg
	Semitrave di base - Base half beam - Semiviga base - Fundamentkreuzträger - Semipoutre de chassis - Полу-балка основания		3,15 m	0,63 m	1,00 m	2	1315 kg
	Telaio 1 - Frame 1 - Chassis 1 - Chassis 1 - Cadre 1 - Шасси 1		2,03 m	0,20 m	0,88 m	1	145 kg
	Telaio 2 - Frame 2 - Chassis 2 - Chassis 2 - Cadre 2 - Шасси 2		2,03 m	0,20 m	0,88 m	1	145 kg
	Piede di base - Base foot - Pie base - Basisfuß - Pied de base - базовая стопа		0,42 m	0,42 m	0,65 m	4	86 kg
Traliccio per sopraelevazione - Section for external climbing - Treillis pour l'élévation externe - Sección para elevación externa - внешней секцией для подъема TM21			2,49 m	2,14 m	2,98 m	1	1815 kg
Gabbia di telescopaggio - Telescoping cage - Teleskopkäfig - Cage télescopique TM21			11,92 m	3,80 m	6,60 m	1	8400 kg

MORITSCH CRANES S.R.L.

Via Ramentera, 52
32035 Santa Giustina - BL - Italy
+39 0437 1840396 - info@moritsch.it
www.moritsch.it